



EverExceed[®] Patented Robust AGM Technology

ST-6150
VALVE REGULATED
LEAD ACID BATTERY
FOR TELECOM / ELECTRIC
UTILITY APPLICATIONS
6V 150 AH @ 10 HR to 1.80VPC
6V 169 AH @ 20 HR to 1.75VPC

**LONG
DURATION**

**HIGH
PERFORMANCE**



Innovative Features


- ◆ Thick positive plate design for maximum service float life 12 years design life @ 20°C(68°F).
- ◆ Valve regulated lead acid battery (VRLA).
- ◆ High-Compression Absorbed Glass Mat technology (AGM) for greater than 99% recombination efficiency.
- ◆ Proprietary Fixed Orifice Plate Pasting technology applying active materials on both sides of the grid for consistent cell-to-cell performance, higher capacity and uniform grid protection.
- ◆ Operates at a low internal pressure.
- ◆ Heavy duty insert copper alloy terminals for ease of assembly, reduced maintenance and increased safety.
- ◆ Advanced lead tin calcium alloy, reduces grid corrosion and promotes long battery life.
- ◆ Over-sized, through the partition inter-cell welds provide low resistance connections, with minimal power loss.
- ◆ Flame arresting, low pressure safety release venting system for individual cells, recognized per U.L. 924.
- ◆ Multicell design for ease of installation and maintenance
- ◆ Horizontal or vertical operation.
- ◆ **Standard:**
Reinforced ABS (UL 94HB) container and cover
- ◆ **Optional:**
Flame-retardant reinforced ABS container and cover compliant with U.L.94 V-0 with an Oxygen limiting Index of greater than 28%.

6 VOLTS - 150 AMPERE HOUR @ 10 HOUR RATE

AH Capacity to 1.80VPC @ 68°F (20°C)




End Point Volts/Cell	60min	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr
1.80	96.4	108	114	122	128	133	143	150	153	165

For Telecom / Electric Utility Applications



Standard Range VRLA

EverExceed[®]
power your applications



Length: 260mm
Width: 180mm
Height: 252mm

Electrical Specifications

Cells Per Unit	Voltage Per Unit	Weight	Electrolyte	Maximum Discharge Current@5s	Short Circuit Current	Internal Resistance (mΩ)
3	6.42	52.8lbs 24.0kg	SG = 1.300	1500 Amps	4500 Amps	3.0

Capacity	169 Ah @ 20 hr. rate to 1.75 volts per cell @ 68°F (20°C). 150 Ah @ 10 hr. rate to 1.80 volts per cell @ 68°F (20°C).
Applicable Operating Temperature Range	-40°F (-40°C) to +158°F (70°C).
Ideal Operating Temperature Range	+68°F (+20°C) to +82.4°F (28°C).
Floating Charging Voltage	6.75 to 6.90 VDC/unit Average at 68°F~77°F (20°C~25°C).
Recommended Maximum Charging Current Limit	37.5 Amperes (0.25C10 Amperes)
Equalization and Cycle Service Charging Voltage	7.05 to 7.20 VDC/unit Average at 68°F~77°F (20°C~25°C).
Maximum AC Ripple (Charger)	0.5% RMS or 1.5% P-P of float charge voltage recommended for best results. Maximum voltage allowed = 1.4% RMS (4% P-P). Maximum current allowed = 0.75 amperes RMS (C/10).
Self Discharge	EverExceed Standard Range batteries may be stored for up to 12 months at 68°F~77°F (20°C~25°C) and then a freshening charge is required. For higher temperatures the time interval will be shorter.
Accessories	Inter unit connectors racks and cabinet systems are available.
Terminal: Inserted	Threaded copper alloy insert terminal
Terminal Hardware Initial Torque: Inserted Terminal	11 N-m

Constant Power Discharging Ratings - Watts Per Cell @ 20°C (68°F)

End Point Volts/Cell	15min	30min	60min	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr
1.85	444	285	182	129	104	75.9	60.2	49.9	34.1	28.4	24.2	16.1
1.80	453	291	186	138	110	78.9	62.3	51.8	35.7	29.6	25.3	16.5
1.75	478	302	192	140	112	80.9	63.8	52.8	36.3	30.2	25.8	16.8

Constant Current Discharging Ratings - Amperes Per Cell @ 20°C (68°F)

End Point Volts/Cell	15min	30min	60min	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr
1.85	241.1	154.8	94.5	67.1	53.9	38.7	30.4	25.2	17.0	14.0	11.9	7.70
1.80	246	158	96.4	71.7	57.1	40.8	32.0	26.5	18.0	15.0	12.8	8.25
1.75	264	164	100	72.9	58.8	42.0	32.9	27.2	18.6	15.4	13.1	8.47

Note: Batteries to be mounted with 0.5 in (1.25 cm) spacing minimum and free air ventilation.
Specifications subject to change without notification.

