

LONG DURATION



**EVEREXCEED FT GELLYTE TECHNOLOGY,
EXCELS IN TELECOM APPLICATION**

FGL12-250

**GELLED VALVE REGULATED
LEAD ACID BATTERY (GVR)
FOR CYCLING APPLICATIONS**

12V 250AH @ 10HR RATE to 1.80VPC

12V 282AH @ 20HR RATE to 1.75VPC

12V 314AH @ 100HR RATE to 1.75VPC

Can be used in any orientation. Upright, side or end mounting recommended;

Reinforced ABS case and cover – flame retardant material
UL 94 V-0 on request.

Innovative Features


- 6V & 12V AGM blocs with gel;
- Special design comply with telecom 19"/ 23" cabinet for space limitation;
- The success of EverExceed FT Gellyte batteries comes from the internationally superior EverExceed FT Gellyte technology;
- Exceptional energy storage capacity combined with long life - BCI Classification;
- Virgin Pure Lead Tin and thick positive plate technology design for maximum service float life - 12 years design life @ 20°C (68°F);
- Thick positive plate plus optimized plate alloy to anti-corrosion;
- UL Recognized component;
- Designed in accordance with IEC 60896-21/-22;
- Spill-proof and leak-proof;
- Maintenance-free (no topping up) during the whole service life due to EverExceed Gel technology;
- Proprietary Fixed Orifice Plate Pasting technology applying active materials on both sides of the grid for consistent cell-to-cell performance, higher capacity and uniform grid protection.
- Flame-arresting one-way pressure-relief vent for safe and long life;
- Electrolyte in solid gel form will not stratify-no equalization charge required;
- Sulfuric acid thixotropic gel, gel powder from Europe leading supplier to ensure the unique performance of gel battery;
- Increased durability and deep cycle ability for heavy-duty applications;
- Fully tank formed grid Lead Calcium Tin plate ensures voltage matching between cells;
- Shelf life up to 2 years at 20°C (68°F), very low gassing due to internal gas recombination;

12 VOLTS - 250 AMPERE HOUR @ 10 HOUR RATE

AH Capacity to 1.80VPC @ 20°C (68°F)




End Point Volts/Cell	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr	24hr	48hr	72hr	100hr
1.80	161	182	196	206	213	238	250	252	276	279	287	297	307

For Telecommunication / Solar / Marine / Mobility Applications



FT GELLYTE RANGE VRLA

EverExceed[®]
power your applications



Length: 520mm
Width: 269mm
Height: 225mm

Electrical Specifications						
Cells Per Unit	Voltage Per Unit	Weight	Electrolyte	Maximum Discharge Current	Short Circuit Current	Ohms Imped 60 Hz(Ω)
6	12.84	178lbs 80.5kg	SG = 1.300	1589 Amps	4810 Amps	0.00260

Capacity	250 Ah @ 10 hr. rate to 1.80 volts per cell @ 20°C (68°F). 282 Ah @ 20 hr. rate to 1.75 volts per cell @ 20°C (68°F). 314 Ah @ 100 hr. rate to 1.75 volts per cell @ 20°C (68°F).
Applicable Operating Temperature Range	-40°F (-40°C) to +158°F (70°C).
Ideal Operating Temperature Range	+68°F (+20°C) to +90°F (32°C).
Floating Charging Voltage	13.5 to 13.8 VDC/unit Average at 68°F (20°C).
Recommended Maximum Charging Current Limit	0.2C20 amperes (56.4 amperes @ 100% depth of discharge) @ 20 hr. rate.
Equalization and Cycle Service Charging Voltage	14.1 to 14.4 VDC/unit Average at 68°F (20°C).
Maximum AC Ripple (Charger)	0.5% RMS or 1.5% P-P of float charge voltage recommended for best results. Maximum voltage allowed = 1.4% RMS (4% P-P). Maximum current allowed = 14.1 amperes RMS (C/20).
Self Discharge	EverExceed Front Access FT Gellyte Range batteries may be stored for up to 24 months at 68°F (20°C) and then a freshening charge is required. For higher temperatures the time interval will be shorter.
Accessories	Inter unit connectors racks and cabinet systems are available.
Terminal: Inserted	Threaded copper alloy insert terminal
Terminal Hardware Initial Torque: Inserted Terminal	20 NM

Constant Power Discharging Ratings - Watts Per Cell @ 20°C (68°F)										
End Point Volts/Cell	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr	24hr
1.85	195	169	121	95.3	79.3	55.9	46.1	39.4	25.7	22.1
1.80	206	174	127	100	83.6	58.7	48.8	41.8	27.4	23.3
1.75	209	177	129	102	85.3	59.7	49.8	42.6	27.9	23.7

Constant Current Discharging Ratings - Ampere per Cell @ 20°C (68°F)													
End Point Volts/Cell	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr	24hr	48hr	72hr	100hr
1.85	101	85.4	61.6	48.6	40.3	28.2	23.2	19.8	12.9	11.1	5.78	3.99	2.97
1.80	108	90.6	65.5	51.5	42.7	29.7	25.0	21.0	13.8	11.7	6.00	4.13	3.07
1.75	110	92.7	67.0	52.8	43.8	30.5	25.4	21.6	14.1	12.0	6.15	4.22	3.14

Note: Busbar connection designed for 0.375" (1.0 cm) battery spacing.
Batteries to be mounted with 0.3" (0.75 cm) spacing minimum and free air ventilation.
Specifications subject to change without notification.

