



EverExceed<sup>®</sup> Patented Robust AGM Technology

# HIGH PERFORMANCE



## ST-6300

VALVE REGULATED  
LEAD ACID BATTERY  
FOR TELECOM / ELECTRIC  
UTILITY APPLICATIONS

6V 300 AH @ 10 HR to 1.80VPC  
6V 344 AH @ 20 HR to 1.75VPC


# LONG DURATION

### Innovative Features

- ☑ Thick positive plate design for maximum service float life 12 years design life @ 20°C(68°F).
- ☑ UL Recognized component.
- ☑ Valve regulated lead acid battery (VRLA).
- ☑ High-Compression Absorbed Glass Mat technology (AGM) for greater than 99% recombination efficiency.
- ☑ Proprietary Fixed Orifice Plate Pasting technology applying active materials on both sides of the grid for consistent cell-to-cell performance, higher capacity and uniform grid protection.
- ☑ Operates at a low internal pressure.
- ☑ Heavy duty insert copper alloy terminals for ease of assembly, reduced maintenance and increased safety.
- ☑ Advanced lead tin calcium alloy, reduces grid corrosion and promotes long battery life.
- ☑ Over-sized, through the partition inter-cell welds provide low resistance connections, with minimal power loss.
- ☑ Flame arresting, low pressure safety release venting system for individual cells, recognized per U.L. 924.
- ☑ Multicell design for ease of installation and maintenance
- ☑ Horizontal or vertical operation.
- ☑ **Standard:**  
Reinforced ABS (UL 94HB) container and cover
- ☑ **Optional:**  
Flame-retardant reinforced ABS container and cover compliant with U.L.94 V-0 with an Oxygen limiting Index of greater than 28%.






6 VOLTS - 300 AMPERE HOUR @ 10 HOUR RATE										
AH Capacity to 1.80VPC @ 68°F (20°C)										
End Point Volts/Cell	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr	24hr
1.80	217	231	244	256	266	288	300	307	333	338

### For Telecom / Electric Utility Applications



# Standard Range VRLA

**EverExceed**<sup>®</sup>  
power your applications



Length: 295mm

Width: 178mm

Height: 345mm

## Electrical Specifications

Cells Per Unit	Voltage Per Unit	Weight	Electrolyte	CCA at -18°C(0°F)	Short Circuit Current	Ohms Imped 60 Hz(Ω)
3	6.42	104lbs 47kg	SG = 1.3000	1650 Amps	6500 Amps	0.0014

<b>Capacity</b>	344 Ah @ 20 hr. rate to 1.75 volts per cell @ 68°F (20°C). 300 Ah @ 10 hr. rate to 1.80 volts per cell @ 68°F (20°C).
<b>Applicable Operating Temperature Range</b>	-40°F (-40°C) to +158°F (70°C).
<b>Ideal Operating Temperature Range</b>	+68°F (+20°C) to +82.4°F (28°C).
<b>Floating Charging Voltage</b>	6.75 to 6.90 VDC/unit Average at 68°F~77°F (20°C~25°C).
<b>Recommended Maximum Charging Current Limit</b>	0.25C20 amperes (86 amperes @ 100% depth of discharge) @ 20 hr. rate.
<b>Equalization and Cycle Service Charging Voltage</b>	7.20 to 7.40 VDC/unit Average at 68°F~77°F (20°C~25°C).
<b>Maximum AC Ripple (Charger)</b>	0.5% RMS or 1.5% P-P of float charge voltage recommended for best results. Maximum voltage allowed = 1.4% RMS (4% P-P). Maximum current allowed = 17.2 amperes RMS (C/20).
<b>Self Discharge</b>	EverExceed Standard Range batteries may be stored for up to 12 months at 68°F~77°F (20°C~25°C) and then a freshening charge is required. For higher temperatures the time interval will be shorter.
<b>Accessories</b>	Inter unit connectors racks and cabinet systems are available.
<b>Terminal: Inserted</b>	Threaded copper alloy insert terminal
<b>Terminal Hardware Initial Torque: Inserted Terminal</b>	11 N-m

## Constant Power Discharging Ratings - Watts Per Cell @ 20°C (68°F)

End Point Volts/Cell	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr	24hr
1.85	260	214	151	119	99.3	68.5	57.1	49.4	32.5	26.8
1.80	278	219	157	125	104	71.4	59.4	50.8	33.3	28.2
1.75	287	227	160	127	106	72.5	60.5	51.7	34.0	28.7

## Constant Current Discharging Ratings - Ampere Per Cell @ 20°C (68°F)

End Point Volts/Cell	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr	24hr
1.85	136	108	77	60.5	50.2	34.8	28.7	24.3	16.0	13.2
1.80	145	115	81.9	64.1	53.4	36.1	30.0	25.6	16.8	14.1
1.75	147	118	83.6	65.8	54.1	36.9	30.9	26.4	17.2	14.5

**Note:** Batteries to be mounted with 0.5 in (1.25 cm) spacing minimum and free air ventilation.  
Specifications subject to change without notification.

